



KENT T4 Power IGU

The Kent Paver in Ground Power Unit, **Type 4** unit is an ideal product for trading areas, open air areas with events and exhibitions where temporary power is required. This model, Type 4 has a 760mm x 600mm top recessed cover.

The Type 4 was designed to take 4nr 32a 3 phase sockets. The housing can take other combinations smaller than this including 16A, 32A, or 63A Single Phase or Three Phase sockets. An additional data panel with 1 to 4 RJ45 datapoints or XLR audio points can also be added to this unit along with the sockets.

The lids can be closed during operation, this necessitates a 500mm overall depth.

The hinged recessed cover ensures the units are unobtrusive when not in-use. The In Ground Power Units covers are manufactured in accordance with FACTA and BS EN124 standards. The covers are suitable for 60mm deep paving blocks and are manufactured to meet required loadings. They are fabricated in grade 316 stainless steel as standard.



- Features**
- ❑ Gas Rams
 - ❑ Up to 4nr IP67 32a 3 Phase sockets
 - ❑ Slam lock
 - ❑ Secondary secure holding down lock
 - ❑ Suitable for market trading areas
 - ❑ 110mm diameter drain outlet point

- Designed for**
- ❑ 1nr 16 Amp 1 Phase plus 3nr 32 amp 3 Phase sockets or
 - ❑ 4nr 32 Amp 1 Phase sockets or
 - ❑ 2nr 63 Amp 3 Phase sockets (650mm deep unit)

- Other Options**
- ❑ RJ45 Datapoints
 - ❑ XLR Audio Connection
 - ❑ Fiber Connections

Product Code	Visible Frame Size	Unit Depth	Cable Duct (Ø)
KIGU760/600	760mm x 600mm	500mm	125mm
KIGU850/600-Data	850mm x 600mm	500mm	125mm
KIGU850/600-63A+Data	850mm x 600mm	650mm	125mm



Specify Kent IGU– Type 4 Unit; 760mm x 600mm top; with a 500mm depth (Closed Use); Grade 316 Stainless Steel; EP031– 3nr 32 amp 3 phase plus 1nr 16 amp 1 phase Sockets



KENT T4 Power IGU



This box is used where there are multiple carts with heavy power requirements.
Widen the box to add a strip of Data.
Deepen the Box to use > 1nr 63 Amp 3 Phase Power.

